



Micro Diameter

Type No. 型號	Diameter 刃徑 d1	Flute Length 刃長 l ₁	Taper Angle 斜頸 α	Taper Neck 斜頸長 l ₂	O. A. L. 全長 l ₃	Shank Dia. 柄徑 d2
MBN2AL0103-6	R 0.5	2	3°	32	75	6
MBN2AL0105-6	R 0.5	2	5°	32	75	6
MBN2AL0203-6	R 1.0	4	3°	27	100	6
MBN2AL0205-6	R 1.0	4	5°	27	100	6
MBN2AL0315-6	R 1.5	6	1.5°	35	100	6
MBN2AL0303-6	R 1.5	6	3°	35	100	6
MBN2AL0415-6	R 2.0	8	1.5°	28	100	6
MBN2AL0403-6	R 2.0	8	3°	28	100	6
MBN2AL0603	R 3.0	12	3°	32	100	8
MBN2AL0605	R 3.0	12	5°	35	100	10
MBN2AL0603B	R 3.0	12	3°	32	150	8
MBN2AL0605B	R 3.0	12	5°	35	150	10
MBN2AL0803	R 4.0	16	3°	36	100	10
MBN2AL0805	R 4.0	16	5°	39	100	12
MBN2AL0803B	R 4.0	16	3°	36	150	10
MBN2AL0805B	R 4.0	16	5°	39	150	12
MBN2AL1003	R 5.0	20	3°	40	100	12
MBN2AL1003B	R 5.0	20	3°	40	150	12
MBN2AL1205	R 6.0	24	5°	47	100	16
MRN2AL1205B	R 6.0	24	5°	47	150	16



High Speed Cutting
& High Hard Cutting

d1 (mm)	d1(mm) tolerance
R1	±0.01
R1.5	±0.01
R2	±0.01
R2.5	±0.01
R3	±0.01
R4	±0.01
R5	±0.01
R6	±0.015

Shank(mm) (h6)	d2(mm) tolerance
Ø 6	⁰ _{-0.008}
Ø 8	⁰ _{-0.008}
Ø 10	⁰ _{-0.009}
Ø 12	⁰ _{-0.011}
Ø 16	⁰ _{-0.011}